

BML-Controls

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWBarMenu (BWCtrl)	barmenu	rendermode (E:professional/system)	<u>menu</u>	-	-	-
BWBorderCtrl (BWCtrl)	-	border (E:None/FixedSingle/Fixed3D) borderref (S)	<u>xborder</u>	-	-	-
BWBrowser (BWCtrl)	browser	src (S) usemenu (B)	-	setSrc back forward home blank stop print printDefault printPreview pageSetup properties	cangobackchange d documentcompleted navigating	-
BWButton (BWValCtrl)	button	def (B)	<u>img</u>	setDefault	-	-
BWCheckbox (BWValCtrl)	checkbox	textalign (E:top/middle/bottom + left/center/right) checkalign (E:left/right/topleft/topright) checkstate (E:unchecked / checked / indeterminate) tri (B)	-	setCheckState setThreeState setTextAlign	statechange statechanged pstatechanged	checked checkstate
BWCheckMenuItem (BWMenuItem)	mci	checked (B)	-	-	mouseenter mouseexit	-
BWChoice (BWCtrl)	choice	edit (B) select (I) sorted (B) valselect (B) align (E:left/center/right) hint (S) padding (I) value (S)	-	selectItem addItems insertItems removeItems setText	selected textupdate pselectionchanged	pos nid val

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
		maxvis (I) acmode (E:none/suggest/append/suggestappend)				
BWCircle <u>(BWOpaqueDeco)</u>	circle	-	-	-	-	-
BWCJScript	cjscript	-	-	-	-	-
BWCompound <u>(BWCtrl)</u>	compound	border (E) scroll (E:none/vertical/both) ifocus (S)	barmenu browser button checkbox choice compound datagrid designpane designgrid designtoolbox editor entry label list tmenu[] notebook picturebox progress radiobutton tstyle[] tborder[] syntaxeditor toolbar toolstrip tree line rect circle group img	addControls removeControls	layouted	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWCtrl <u>(BWElement)</u>	-	state (E:initial required erroneous disabled readonly) tabindex (I) visible (B) rolocked (B) busyactive (B)	<u>pos</u> <u>keys</u> <u>events</u> <u>tooltip</u> <u>content</u> <u>contextmenu</u>	setContent setErroneous setRequired setState setFocus setVisible setCtxMenu setStyleRef setStyle addEvents removeEvents setTooltip	focuslost focusgot clicked validate created resized pcontentchanged pvstatechanged exposed	width height
BWContextMenu	contextmenu	-	<u>menu</u>	-	-	-
BWDataGrid <u>(BWCtrl)</u>	datagrid	extendable (B) autosize (E:none / cols / rows / all) header (E:none / cols / rows / all) selmode (E:CellSelect/FullRowSelect/FullColumnSelect/RowHeaderSelect/ColumnHeaderSelect) multisel (B)	-	editCell selectRows selectCols selectCells insertRows removeRows clearSelection	beginedit endedit celclicked cellcontentclicked celldoubleclicked headerclicked rowclicked rowadded selectionchanged	colidx rowidx colid rowid cellid val
BWDateTimePicker <u>(BWCtrl)</u>	datetime	spin(B) format(S) e.g. "ddd dd.MM.yyyy hh:mm"	-	setDateTime setMinDateTime setMaxDateTime setFormat setSpinMode	validate valuechanged	val jval lsvl ftval
BWDeco <u>(BWElement)</u>	-	-	<u>pos</u>	-	-	-
BWDesignPane <u>(BWCtrl)</u>	designpane	-	selection	select remove insert clear deploy	removed modified added selected deploy	member serialized cid urlid
BWDesignProps	designprops	-	-	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
(BWCtrl)						
BWDesignToolbox (BWToolbar)	designtoolbox	-	-	-	-	-
BWDialog (BWCtrl)	dialog	title (S) baseuri (S) width (I) height (I) imgSrc (S) sizeable (B)	<u>tstyle[]</u> <u>tmenu[]</u> <u>portal</u> <u>portlet[]</u>	-	closerequest closed	-
BWEeditor (BWValCtrl)	editor	tab (B) wrap (B) istart (I) iend (I) scroll (E:none/vertical/horizontal/both)	-	selectAll selectFromTo cut copy paste	-	-
BWElement	-	id (S) stylerref (S)	<u>style</u> <u>script</u> <u>prop[]</u>	-	-	id
BWEntry (BWValCtrl)	entry	password (B) maxlen (I) istart (I) iend (I) align (E:left/center/right) hint (S) mask (S)	-	selectAll selectFromTo cut copy paste	modified	-
BWEvent	event	name (S) method(S)	-	-	-	-
BWEvents	events	-	<u>event[]</u>	-	-	-
BWExtBorder	xborder	id (S)	style (E:none/flat/sunken/bump/etc hed/raised) color (S) icolor (S) width (I)	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWGroup (BWDeco)	groupbox	title (S)	-	-	-	-
BWGroupBox (BWCompound)	compoundbox	title (S)	-	-	-	-
BWImage (BWDeco)	img	src (S) mode (E:unscaled/scaled/centered/cropped/aligned) align (E:top/middle/bottom + left/center/right)	-	-	-	-
BWKey	key	name [<C+A+S->key] method (S) global (B)	-	-	-	-
BWKeys	keys	-	key[]	-	-	-
BWLabel (BWValCtrl)	label	align (E:top/middle/bottom + left/center/right) for (S) ellipsis (B)	-	-	-	-
BWLayout	pos	Anchors (relative [ppm]): aox (I) aoy (I) acx (I) acy (I) Offsets (absolute): eox (I) eoy (I) ecx (I) ecy (I) rel (E:none/xflow/yflow) hmin (I) wmin (I) unit (E:pixel/sysfont) asmode (E:none/width/height) policy (E:always/visible)	-	-	-	-
BWLine (BWDeco)	line	-	-	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWList <small>(BWCtrl)</small>	list	checkstyle (B) editable (B) sortable (B) startidx (I) select (I) multisel (B)	-	clear removeItems setItemsChecked setItemsSelected setItemsEnabled setIdTooltip setItemsStyleRef addItems insertItems	checkrequest uncheckrequest check uncheck checkchanged selected deselected selectionchanged itemclicked itemdoubleclick d colsort pselectionchange d	nids nidxs pos val nid checked
BWMenu <small>(BWElement)</small>	menu	action (S)	<u>mi[]</u> <u>mci[]</u> <u>msub[]</u> <u>msep[]</u>	-	-	-
BWMenuItemElement <small>(BWElement)</small>	-	label (S) align (E:left/right)	-	-	-	-
BWMenuItem <small>(BWMenuItemElement)</small>	mi	action (S) accel (S) imgSrc (S) imgRes (S)	<u>events</u>	-	mouseenter mouseleave	-
BWMenuItemSubItem <small>(BWMenuItem)</small>	msub	-	<u>mi[]</u> <u>mci[]</u> <u>msub[]</u> <u>msep[]</u>	-	-	-
BWMenuItemSeparator <small>(BWMenuItemElement)</small>	msep	-	-	-	-	-
BWMonthCalendar <small>(BWCtrl)</small>	mcalendar	scrollchange (I) date (S)	-	setDate	datechanged dateselected	date start end
BWNNotebook	notebook	tabalign (E:top/bottom/left/right)	bookpage[]	selectPage	selectionchanged	tabid

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
(BWCtrl)		tabwidth (I)		insertPage removePage setPageContent	selecting deselecting	tabidx
BWOpaqueDeco (BWDeco)	-	width (I) fill (B)	-	-	-	-
BWPictureBox (BWCtrl)	picturebox	border (E:None/FixedSingle/Fixed3D) sizemode (E:Normal/StretchImage/AutoSize/CenterImage/Zoom)	<u>img</u>	-	-	-
BWPortal	portal	defaulttarget (S)	<u>portletcontainer[]</u> <u>portletpane</u>	-	-	-
BWPortlet (BWCompound)	portlet	title (S) target (S) vstate (E:normal/min/max) position (E:top/bottom) mode (E:normal/sticky) width (I) height (I) titlebar (B)	-	-	-	-
BWPortletContainer (BWPortletPane)	portletcontain er	split (E:H/V) fixed (B)	<u>portletcontainer</u> <u>portletpane</u>	-	-	-
BWPortletPane	portletpane	px (S) py (S) dx (S) dy (S) id (S) cls (S) radio (S)	-	-	-	-
BWProgress (BWCtrl)	progress	min (I) max (I) val (I) step (I) barstyle (E:Blocks/Continuous/Marquee)	-	setVal setMin setMax setMinMax setValues setBarStyle	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWRadioButton <u>(BWValCtrl)</u>	radiobutton	textalign (E:top/middle/bottom + left/center/right) checkalign (E:left/right) group (S) checked (B)	-	check setGroup	checked	checked
BWRect <u>(BWOpaqueDeco)</u>	rect	-	-	-	-	-
BWProperty	prop	name (S) value (S)	-	-	-	-
BWRadioButton <u>(BWValCtrl)</u>	radiobutton	textalign (E:top/middle/bottom + left/center/right) checkalign (E:left/right) group (S) checked (B)	-	check setGroup	checked	checked
BWRect <u>(BWOpaqueDeco)</u>	rect	-	-	-	-	-
BWScorllbar <u>(WCtrl)</u>	scrollbar	direction (E:horizontal/vertical) min (I) max (I) val (I)	-	setRange setValue	onScroll	val type endscroll tracking first last
BWSlider <u>(WCtrl)</u>	slider	dir (E:horz/vert) min (I) max (I) val (I)	-	setRange setValue	scroll valuechanged pvaluechanged	val
BWStyle	style	id (S)	color backgroundcolor padding width font fontstyle fontsize fontfamily border borderleft	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
			borderright bordertop borderbottom			
BWSyntaxEditor (BWValCtrl)	syntaxeditor	syntax (E:xml/java/csharp/jscript/css/html) wrap (B) istart (I) iend (I) lines (B)	-	findReplaceAll selectAll selectFromTo setSyntax	-	-
BWToolbar (BWCtrl)	toolbar	rendermode (E:professional/system) gripstyle (E:visible/hidden)	tbbutton tbcbutton tbmbutton tblabel tbchoice tbentry tbseparator	removelds addElements	-	-
BWToolbarButton (BWToolbarElement)	tbutton	-	val img	-	-	-
BWToolbarCheckButton (BWToolbarButton)	tbcbutton	checked (B)	-	-	check uncheck checkchanged	-
BWToolbarChoice (BWToolbarElement)	tbchoice	-	items	-	selected	-
BWToolbarElement (BWElement)	-	-	events tooltip	setEnabled setText	click	-
BWToolbarEntry (BWToolbarElement)	tbentry	-	val	-	focuslost validate	-
BWToolbarLabel (BWToolbarElement)	tblabel	-	val	-	-	-
BWToolbarMenu (BWElement)	tbmenu	-	items events	-	selected	-
BWToolbarMenuItem (BWToolbarElement)	tbmbutton	-	tbmenu	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BWToolbarSeparator <small>(BWToolbarElement)</small>	tbseparator	-	-	-	-	-
BWTooltip	-	-	tth (S) ttb (S)	-	-	-
BWTree <small>(BWCtrl)</small>	tree	startidx (I) checkstyle (B) padding (I) seldix (I) selid (S)	-	clear removeItems setItemsChecked setItemsExpanded setItemsSelected setItemImage setItemsStyle revealItems removeSubItems setSubItems addItems insertItems	selected deselected check checkrequest uncheck uncheckrequest expand collapse expanded collapsed nodeclicked nodedoubleclicked	pos val nid
BWValCtrl <small>(BWBorderCtrl)</small>	-	-	-	-	-	val

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BEvent	bevent	method (S) name (S) type (E:xmlrpc:/client:/tel:) category (E:none/laction/vaction)	-	-	-	-
BStyle	style	id (S) select (tagname='class')	<bw:font>family,size,style</bw:font> <bw:color>value</bw:color> <bw:backcolor>value</bw:backcolor> <bw:backbrush>value</bw:backbrush>	-	-	-
BLayout	layout	aox, aoy, ayx, axy (I) eox, eoy, ecx, ecy (I) rel (E:xflow/yflow) asmode (E:width/height)	-	-	-	-
BView	-	id (S) tabindex (I)	<u>layout</u> <u>llayout</u> <u>style</u>	setContent	-	-
BControl (BView)	-	state (E:required/errorneous/disabled/initial)	bw:events/bw: <u>bevent</u> bw:content	addEvents setState	clicked	id
BCompound (BControl)	compound	-	<u>browser</u> <u>button</u> <u>checkbox</u> <u>choice</u> <u>compound</u> <u>editor</u> <u>entry</u> <u>grid</u> <u>label</u> <u>mainform</u>	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
			<u>mlist</u> <u>picturebox</u> <u>searchentry</u> <u>segment</u> <u>sibs</u> <u>tabbar</u> <u>tabcontainer</u> <u>toolbar</u> <u>viewcontrol</u> <u>img</u> <u>line</u> <u>rect</u> <u>text</u> <u>tstyle</u>			
BWebBrowser <small>(BControl)</small>	browser	secure (E:on/off) src (S)	-	setSrc	-	-
BButton <small>(BControl)</small>	button	-	-	-	-	-
BSwitch <small>(BControl)</small>	bcheckbox	-	-	setCheckState	-	-
BChoice <small>(BControl)</small>	choice	-	bw:content/bw:choicelist/bw:body/bw:li	selectItem	validate	id val pos nid
BEditor <small>(BControl)</small>	editor	-	-	-	-	-
BEntry <small>(BControl)</small>	entry	hint (S)	<bw:kbd type="" autocap="" autocorrect="" /> <bw:ovltext align="left">Name</bw:ovltext >	-	-	-
BGridView <small>(BControl)</small>	grid	-	bw:content/<bw:gi>	-	selected validate	id iid

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BLabel <u>(BControl)</u>	label	<td>-</td> <td>-</td> <td>-</td> <td>-</td>	-	-	-	-
BMainForm <u>(BControl)</u>	mainform	-	<u>fgroup</u>	selectItem setCheckState setState setGroupVisible setHint setContent insertElement removeElement setError	-	-
BList <u>(BControl)</u>	list	style (E:plain/grouped/small)	<u>bw:mcontent/bw:mdata/mli</u>	addItems updateItems clear	selected validate	id val pos
BListItem	mli	-	mlil mlir mlit mlid mlia mlis mlip mlif mliu <u>compound</u>	-	-	-
BImage <u>(BControl)</u>	picturebox	-	<bw:img src="up.png" />	-	-	-
BSearchEntry <u>(BControl)</u>	searchentry	kbd (E:url) book (E:yes/no) hint (S)	-	-	validate	id val
BSegment <u>(BControl)</u>	segment	sel (I)	<bw:sbutton img="up.png" label="Prev"/>	-	itemclicked	id val idx

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BSibsContainer <u>(BControl)</u>	sibs	pageindicator (B)	<u>sib</u>	-	-	-
BSibView <u>(BCompound)</u>	sib	img (S) label (S)	-	-	-	-
BTabBar <u>(BControl)</u>	tabbar	-	<bw:ttbutton id="1" img="up.png" title="Next" />	-	validate	id
BTabContainer <u>(BView)</u>	tabcontainer	-	<u>tab</u>	setView	-	-
BTab <u>(BCompound)</u>	tab	id (S) img (S) title (S)	<u>view</u>	-	-	-
BToolBar <u>(BControl)</u>	toolbar	style (E:opaque/translucent)	<u>tbutton</u> <u>segment</u>	setToolbarItems setItemsEnabled	validate	id
BBarButton	tbutton	id (S) action (S) category (S) img (S) label (S) sys (E:done/cancel/edit/save/add/reply/search/stop/camera/space/fxspace)	-	-	-	-
BNavContainer <u>(BControl)</u>	viewcontrol	-	<u>view</u>	setView	-	-
BNavView <u>(BCompound)</u>	view	title (S) backlabel (S)	-	-	-	-
BCell <u>(BCell)</u>	fgroup	-	<u>fheader</u> <u>items</u> <u>ffooter</u>	-	-	-

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
BCell (BCell)	items	action	form fssel fmsel fpick flaunch fcmd fbool fint fstring fedit	-	-	-
BCell (BCell)	form	title (S)	fgroup	-	-	-
BBoolCell (BCell)	fbool	action	prompt content event	-	validate	id val sel checkstate
BCmdCell (BCell)	fcmd	style (E:regular/destructive/disabled)	prompt event	-	validate	id
BCell (BCell)	fstring	type (E:number/text/url) autocap (E:none/words/sentences/allchars) autocorrect (E:off/on) kbd (E:next/done) hint (S) secure (B) state (E:initial/required/erroneous/disabled/invisible/readonly)	prompt content event	-	validate closing	id val
BMultiEditCell (BCell)	fedit	height (I oder '*') autocap (E:none/words/sentences/allchars) autocorrect (E:off/on) kbd (E:next/done)	content event	-	validate closing	id val
BCell	fssel	action	prompt	-	validate	id

Element	Tag	Attrs	InnerTags	Commands	Events	EventArgs
(BCell)			<u>content</u>		closing	val pos sel aval
BPickerCell (BCell)	fpick	mode (E:date/time/datetime/span) format (S) action	<u>view</u>	-	validate closing	id val

Legende:

I = Integer
 B = Boolean
 S = String
 E = Enumeration (Aufzählungstyp)

In der Spalte "Element" (erste Spalte) steht in Klammern die unmittelbare Basisklasse. Damit kann die Ableitungshierarchie der Controls verfolgt werden.